

FS5-FL Fireman switch, flush with key

Q N° 070



FS5-FL Fireman switch

- Flush mount



**Standard pattern drop-key
used by the fire services.**

The key is NOT supplied by NACD.

REGULATIONS:

**Compulsory, must be fitted on every vehicle entrance that is a designated fire brigade access route.
Not compulsory for communal pedestrian entrance doors.**

Dimensions:
Backbox 169mmH x 118mmW x 80mmD
Facia with flange: 199mmH x 148mmW

NOTES

Operates with fail safe locking on doors.
This is an override device only.

FS5-FL FIREMAN SWITCH, FLUSH MOUNTED

Flush mounted BS316 grade s.steel anti-vandal.
Standard pattern, drop key fireman switch.

FS

FS5-HS Fireman switch, hooded surface with key

Q N°-072



FS5-HS Fireman switch

- Surface mount
- Preset for post mounting



**Standard pattern drop-key
used by the fire services.**

The key is NOT supplied by NACD.

REGULATIONS:

**Compulsory, must be fitted on every vehicle entrance that is a designated fire brigade access route.
Not compulsory for communal pedestrian entrance doors.**

Dimensions code: 158mmH x 108mmW x 80mmDB x 100mmDT

NOTES

Operates with fail safe locking on doors.
This is an override device only.

FS5-HS FIREMAN SWITCH, HOODED SURFACE

Hooded surface BS316 grade s.steel anti-vandal.
Standard pattern, drop key fireman switch.

FS